



ZERA

MT500
Product Catalogue

Doc.No: 100352708
Version from: 01.07.2024

Device



MT500 Three Phase Current/Voltage Source

Inclusive adjustment and factory calibration for one mains frequency.

Ord.No. **1016732xx**


Calibration	Ord.No.
Factory 50 Hz	xx → 00
Factory 60 Hz	xx → 01
DAkKS 50 Hz	xx → 02
DAkKS 60 Hz	xx → 03

MT500 is designed for generation of test voltage and test current for one test specimen.

Configuration:

- 3~ phase voltage generation up to 300 V (AC)
- 3~ phase current generation up to 12 A (AC)
- Light and compact design

Power Cords



Power cord with protective earth "stackable safety plug to IEC 60320 C13", 2,5 m

For supply via test voltage.

- 3x stackable, spring-loaded 4 mm plugs with rigid insulating sleeve (1x black, 1x blue, 1x yellow/green)
- 1x socket IEC 60320 C13

Ord.No. **100067609**



Power cord "Class I grounded plug type E/F to IEC 60320 C13", 2,5 m

For supply via power socket.

- 1x class I grounded plug type E/F (CEE 7/7), straight
- 1x socket IEC 60320 C13

Ord.No. **M00481006**



Power cord "Plug type B to IEC 60320 C13", 2,5 m

For supply via power socket.

- 1x plug type B
- 1x socket IEC 60320 C13

Ord.No. **X00006459**



Power cord “Plug type I to IEC 60320 C13“, 2.5 m

For supply via power socket.

- 1x plug type I (AS/NZS 3112, 3-pin)
- 1x socket IEC 60320 C13

Ord.No. **X00006460**



Power cord “Plug type G (BS 1363) to IEC 60320 C13“, 2.5 m

For supply via power socket.

- 1x Plug type G (BS 1363)
- 1x socket IEC 60320 C13

Ord.No. **X00009832**



Power cord “Plug type D (BS 546) to IEC 60320 C13“, 1.8 m

For supply via power socket.

- 1x Plug type D (BS 546)
- 1x socket IEC 60320 C13

Ord.No. **100929900**




Power cord “Plug type H” to IEC 60320 C13“, 1.8 m

For supply via power socket.

- 1x Plug type H
- 1x socket IEC 60320 C13

Ord.No. **100929903**

Quick Connection Cable (see also Special Accessories)



Quick connection cable “current/rigid sleeve” for source, MT series, sloped, 2.5 m, phase colours: red/yellow/blue

To prevent connecting faults on the instrument’s side.

- Instrument’s side: 1x 6-pin connector with anti-twist safeguard, 30° sloped.
- Mains side: 6x stackable, spring-loaded 4 mm plugs with rigid insulating sleeve. 2x red, 2x yellow, 2x blue.
- Cable cross-section: 2.5 qmm

Ord.No. **100023452**




Quick connection cable for “voltage/rigid sleeve” for MT series, 2.5 m, phase colours: red/yellow/blue/black

To prevent connecting faults on the instrument's side.

- Instrument's side: 1x 4-pin connector with anti-twist safeguard.
- Mains side: 4x stackable, spring-loaded 4 mm plug with rigid insulating sleeve - 1x red, 1x yellow, 1x blue, 1x black
- Cable cross-section: 2.5 qmm

Ord.No. **100023454**




Quick connection cable “voltage/rigid sleeve” for source-instrument, MT series, 2.5 m, phase colours: red/yellow/blue/black

For the connection of source and reference standard if they are used as separate devices.

Cable length between the devices is 1.65 m.

- Reference standard's side :
 - 1x 4-pin connector with anti-twist safeguard.
 - 1x 4-pin connector (slim) without anti-twist safeguard.
- Mains side: 4x stackable, spring-loaded 4 mm plug with rigid insulating sleeve - 1x red, 1x yellow, 1x blue, 1x black
- Cable cross-section: 2.5 qmm

Ord.No. **100023456**



Quick connection cable “current/rigid sleeve” for source-instrument, MT series, 2.5 m, phase colours: red/yellow/blue


For the connection of source and reference standard if they are used as separate devices.

Cable length between the devices is 1.65 m.

- Instrument's side:
 - 1x 6-pin connector with anti-twist safeguard.
 - 1x 6-pin connector, 30° sloped, with anti-twist safeguard.
- Mains side: 6x stackable, spring-loaded 4 mm plugs with rigid insulating sleeve. 2x red, 2x yellow, 2x blue.
- Cable cross-section: 2.5 qmm

Ord.No. **100023455**

Current and Voltage Cables (see also Special Accessories)



Laboratory cable with stackable plug, red, 2.0 m

Measurement category III (CAT III).

- 2x stackable 4 mm plugs with rigid insulating sleeve
- Lead cross section: 2.5 qmm

Ord.No. **X00007597**



Laboratory cable with stackable plug, yellow, 2.0 m
 Measurement category III (CAT III).
 • 2x stackable 4 mm plugs with rigid insulating sleeve
 • Lead cross section: 2.5 qmm

Ord.No. **X00006907**



Laboratory cable with stackable plug, blue, 2.0 m
 Measurement category III (CAT III).
 • 2x stackable 4 mm plugs with rigid insulating sleeve
 • Lead cross section: 2.5 qmm


Ord.No. **X00007598**



Laboratory cable with stackable plug, black, 2.0 m
 Measurement category III (CAT III).
 • 2x stackable 4 mm plugs with rigid insulating sleeve
 • Lead cross section: 2.5 qmm

Ord.No. **X00006910**


Software



Software SSM3000 / MTVis
 The software runs under Windows 7 or 10.
 • SSM3000: For external control via PC.
 • MTVis: To readout and display saved data.


Ord.No. **100090720**

The software can be downloaded at www.zera.de.



Software option for harmonic measurement, MT400/MT500
 The harmonic measurement displays the value and angle of each single harmonic (voltage and current) up to the 40th in a chart or a diagram. Additionally the sum of all harmonics is displayed.

Ord.No. **100078830**



Software option for curve display, MT400/MT500

For simultaneous display of two curves (voltage and/or current measurement channels). Via the curve display you can see at a glance if the fundamental frequency differs from the sinus curve.

Ord.No. **100078831**

Connectors (see also Special Accessories)



Accessories bag with connection adapters

01 Accessories bag	100214400
03 Spring clip	100606750
04 4 mm plug adapter (banana plug)	X00004962
10 Adapter for terminal blocks	101584400
10 Connecting terminals for current	X00011923
03 4 mm test clips (crocodile clips), slim	X00009329
03 4 mm test clips (crocodile clips), wide	X00010059
10 Fuse, 3.15 A, 5 mm x 20 mm, time-lag	M00460252

Ord.No. **100023727**

Transport (see also Special Accessories)



Transport Case for MT400 / MT500, with cable case

Aluminum case with inlet from rigid foam, designed for

- 1 Instrument
- Accessories

Overall dimensions:

44 cm x 47 cm x 25 cm (H x W x D)

Please clarify whether the case size is suitable for the ordered accessories.

Ord.No. **100023960**



Transport Bag for MT400 / MT500

Nylon bag which is special designed for the instrument.

The bag protects against dust and scratches.

The bag is designed for 1 Instrument

Overall dimensions:

34 cm x 29 cm x 23,5 cm (H x W x D)

Ord.No. **100062802**

Standard Accessories (see also Special Accessories)



Interface cable, RS232, crossed wired (null modem cable)

Connection cable for communication

- 2x D-Sub socket, 9-pin
- Cable length: 3.00 m

Ord.No. **X00010844**



Protection cover for MT series 3xx/400/500

To protect the front plate against mechanical collision during transport without transport case.

Ord.No. **100466700**



Coaxial cable with BNC plug, 2 m

- 2x BNC plug

Ord.No. **Z09548320**

Documentation




Complete Documentation

as pdf files on USB flash drive

Ord.No. **100090716**

Special Accessories



Power cord with protective earth "stackable safety plug to IEC 60320 C13", 2,5 m

For supply via test voltage.

- 3x stackable, spring-loaded 4 mm plugs with rigid insulating sleeve (1x brown, 1x blue, 1x yellow/green)
- 1x socket IEC 60320 C13

Ord.No. **100067610**




Power cord with protective earth “stackable safety plug to IEC 60320 C13”, 2,5 m

For supply via test voltage.

- 3x stackable, spring-loaded 4 mm plugs with rigid insulating sleeve (1x red, 1x black, 1x yellow/green)
- 1x socket IEC 60320 C13

Ord.No. **100067611**

Special Accessories (Quick Connection Cable)



Quick connection cable for “current/rigid sleeve” for MT series, 12 A, 2.5 m, phase colours: yellow/green/violet

To prevent connecting faults on the instrument's side.

- Instrument's side: 1x 6-pin connector with anti-twist safeguard.
- Mains side: 6x stackable, spring-loaded 4 mm plugs with rigid insulating sleeve - 2x yellow, 2x green, 2x violet.
- Cable cross-section: 2.5 qmm

Ord.No. **100023476**




Quick connection cable for “voltage/rigid sleeve” for MT series, 2.5 m, phase colours: yellow/green/violet/black

To prevent connecting faults on the instrument's side.

- Instrument's side: 1x 4-pin connector with anti-twist safeguard.
- Mains side: 4x stackable, spring-loaded 4 mm plug with rigid insulating sleeve - 1x yellow, 1x green, 1x violet, 1x black
- Cable cross-section: 2.5 qmm

Ord.No. **100023418**



Quick connection cable “current/rigid sleeve” for MT series, 12 A, 2.5 m, phase colours: black/brown/white

To prevent connecting faults on the instrument's side.

- Instrument's side: 1x 6-pin connector with anti-twist safeguard.
- Mains side: 6x stackable, spring-loaded 4 mm plugs with rigid insulating sleeve. 2x black, 2x brown, 2x white
- Cable cross-section: 2.5 qmm

Ord.No. **100023493**



Quick connection cable "voltage/rigid sleeve" for MT series, 2.5 m, phase colours: brown/black/white/blue

To prevent connecting faults on the instrument's side.

- Instrument's side: 1x 4-pin connector with anti-twist safeguard.
- Mains side: 4x stackable, spring-loaded 4 mm plug with rigid insulating sleeve - 1x brown, 1x black, 1x white, 1x blue
- Cable cross-section: 2.5 qmm

Ord.No. **100023492**



Quick connection cable "current/rigid sleeve" for MT series, 12 A, 2.5 m, phase colours: black/brown/grey

Reference meter > Unit under test.

To prevent connecting faults on the instrument's side.

- Instrument's side: 1x 6-pin connector with anti-twist safeguard.
- Mains side: 6x stackable, spring-loaded 4 mm plugs with rigid insulating sleeve. 2x black, 2x brown, 2x grey
- Cable cross-section: 2.5 qmm

Ord.No. **100023474**

Special Accessories (Current and Voltage Cables)



Laboratory cable with stackable plug, green, 2.0 m
Measurement category III (CAT III).

- 2x stackable 4 mm plugs with rigid insulating sleeve
- Lead cross section: 2.5 qmm

Ord.No. **X00006908**



Laboratory cable with stackable plug, violet, 2.0 m
Measurement category III (CAT III).

- 2x stackable 4 mm plugs with rigid insulating sleeve
- Lead cross section: 2.5 qmm

Ord.No. **X00006909**



Laboratory cable with stackable plug, brown, 2.0 m
Measurement category III (CAT III).

- 2x stackable 4 mm plugs with rigid insulating sleeve
- Lead cross section: 2.5 qmm

Ord.No. **100414100**

**Laboratory cable with stackable plug, grey, 2.0 m**

Measurement category III (CAT III).

- 2x stackable 4 mm plugs with rigid insulating sleeve
- Lead cross section: 2.5 qmm

Ord.No. **100414103****Laboratory cable with stackable plug, white, 2.0 m**

Measurement category III (CAT III).

- 2x stackable 4 mm plugs with rigid insulating sleeve
- Lead cross section: 2.5 qmm

Ord.No. **100662500****Special Accessories (Connectors)****Connecting terminals for current**

- Insulating screw joint for flexible wire connection max cable size 1,5 ... 16 mm²
- Socket: 4 mm rigid socket in insulator accepting spring-loaded 4 mm plugs with rigid insulating sleeve.

Ord.No. **X00011923****Adapter for terminal blocks**

- Connection via insulated flexible copper conductor.
- Socket: 4 mm rigid socket in insulator, made of brass, accepting spring-loaded 4 mm plugs with rigid insulating sleeve.

Ord.No. **101584400****4 mm plug adapter (banana plug)**

- Plug: 4 mm spring-loaded plug, made of brass.
- Socket: 4 mm rigid socket in insulator accepting spring-loaded 4 mm plugs with rigid insulating sleeve.

Ord.No. **X00004962**



4 mm cable lug adapters

- Cable lug adapter, made of brass for permanent installation, e. g. for connecting screw terminals.
- Socket: 4 mm rigid socket in insulator accepting spring-loaded 4 mm plugs with rigid insulating sleeve.

Ord.No. **X00004963**



Spring clip

- Connection via spring clip.
- Socket: spring-loaded 4 mm plugs with rigid insulating sleeve.

Ord.No. **100606750**



Test plugs for terminal blocks

- Plug: 4 mm test plug, made of brass with spring-loaded plug for connecting into rail mounted terminals with 4 mm sockets.
- Socket: 4 mm rigid socket in insulator accepting spring-loaded 4 mm plugs with rigid insulating sleeve.

Ord.No. **100102400**



4 mm test clips (crocodile clips), wide

- Crocodile clip made of brass with all-round insulation. Toothed jaws for wide grip with surface for fine wire.
- Socket: 4 mm rigid socket in insulator accepting spring-loaded 4 mm plugs with rigid insulating sleeve.

Ord.No. **X00010059**



4 mm test clips (crocodile clips), slim

- Small, slim crocodile clip made of brass with all-round insulation. Toothed jaws for wide grip with surface for fine wire.
- 4 mm rigid socket in insulator accepting spring-loaded 4 mm plugs with rigid insulating sleeve.

Ord.No. **X00009329**



Accessories bag without content
DIN A6, material: polypropylene

Ord.No. **100214400**

Fuse, 3.15 A, 5 mm x 20 mm, time-lag

Ord.No. **M00460252**



Special Accessories (Transport)



Accessories bag

Nylon bag with inlet from rigid foam, designed for

- Test leads
- Scanning head
- Current clamps
- Etc.

Overall dimensions: 41 cm x 31 cm x 16 cm (H x W x D)

Please clarify whether the bag size is suitable for the ordered accessories.

Ord.No. **100148209**

Special Accessories (General)



Adapter "USB to RS232" (32/64 bit), 1.5 m

For use with an external PC/Notebook (32/64 bit) with WINDOWS OS (7, 8, 10).

Ord.No. **101421801**

Readjustment (for Service)




Adjustment of MT500

Note: Calibration and Calibration report are not included.

Ord.No. **100033859**

Calibration (for Service)




Factory Calibration for MT500, 50 Hz
incl. ZERA calibration report.

Ord.No. **100519726**

Load points according to ZERA regulations.
Summary of used load points
can be downloaded at www.zera.de.

Additional load points are subject to charges.



Factory Calibration for MT500, 60 Hz
incl. ZERA calibration report.

Ord.No. **100519727**

Load points according to ZERA regulations.
Summary of used load points
can be downloaded at www.zera.de.

Additional load points are subject to charges.




Factory Calibration
for instrument, each additional
load point for power and energy

Ord.No. **100007093**



Factory Calibration
for instrument, each additional
load point for current and/or voltage

Ord.No. **100007094**




DAkkS DKD-Calibration for MT500, 50 Hz
incl. DKD-Calibration Certificate acc. IEC 17025

Ord.No. **100519626**

Load points according to ZERA regulations.
Summary of used load points
can be downloaded at www.zera.de.

Additional load points are subject to charges.



DAkks DKD-Calibration for MT500, 60 Hz
incl. DKD-Calibration Certificate acc. IEC 17025

Ord.No. **100519627**

Load points according to ZERA regulations.
Summary of used load points
can be downloaded at www.zera.de.

Additional load points are subject to charges.



DAkks DKD-Calibration (acc. IEC 17025)
for instrument, each additional
load point for power and energy

Ord.No. **100006893**



DAkks DKD-Calibration (acc. IEC 17025)
for instrument, each additional
load point for current / voltage

Ord.No. **100006894**

ZERA GmbH
Humboldtstrasse 2a
D-53639 Koenigswinter
Phone: +49 (0)2244 9277-0
E-Mail: zera@zera.de
Internet: www.zera.de
Managing Director: Horst Wächter
Headquarter: Königswinter

Commerzbank Bonn
IBAN: DE29 3804 0007 0113 3131 00
SWIFT (BIC): COBADEFF380

Kreissparkasse Köln
IBAN: DE15 3705 0299 0001 0784 92
SWIFT (BIC): COKSDE33

HRB 7073 Siegburg
VAT-IdNo. DE 218 515 479
WEEE-Reg.Nr. DE 53879641

Notes on using the product catalogue

When ordering, always state the order number.

Pictures can differ from original product.

We follow ZVEI terms of delivery, see on www.zera.de